

In the claims:

*ignore renumbering  
These are claims  
1-5 and 7-10*

<sup>10</sup>  
~~1.~~ (Previously amended) Electromagnetically actuatable valve (1) comprising a magnet part (2), a moveable armature element (7), a spring element (8), and a valve part (9), whereby the magnet part has at least one magnetic coil (4) wound on a coil form (3), a flux concentrating element (5) and a center pole (6), and the valve part (9) has a closing element (11) that cooperates with the armature element (7) and controls the opening and closing of the valve on a valve seat (10), characterized in that the armature element (7) is designed as a clapper-type armature and cooperates with the center pole (6) by way of a damping element (14), wherein the closing element (11) actuated by the armature element (7) to open and close the valve is an umbrella sealing plug with an umbrella membrane.

<sup>11</sup>  
~~2.~~ (Previously amended) Valve according to claim <sup>10</sup>~~1.~~, wherein the armature element (7) and the valve part (9) are contained in a housing.

<sup>12</sup>  
~~3.~~ (Previously amended) Valve according to claim <sup>11</sup>~~2.~~, wherein the armature element (7), the flux concentrating element (5), the closing element (11), the spring element (8), and the damping element (14) are arranged in the housing in a pressure-sealed compartment.

<sup>13</sup>  
~~4.~~ (Previously amended) Valve according to claim <sup>10</sup>~~1.~~, wherein the damping element (14) has a damping stop (13).

<sup>14</sup>  
~~5.~~ (Previously amended) Valve according to claim <sup>10</sup>~~1.~~, wherein the flux concentrating element (5) is designed as a bracket which is situated on the perimeter of the magnetic coil (4).

<sup>15</sup>  
~~6.~~ (Cancelled)

<sup>16</sup>  
~~7.~~ (Previously amended) Valve according to claim <sup>10</sup>~~1.~~, wherein the umbrella sealing plug is flexible and, in particular, consists of silicone rubber.

<sup>17</sup>  
~~8.~~ (Currently amended) ~~Valve according to claim 1~~  
Electromagnetically actuatable valve (1) comprising a magnet part (2), a moveable armature element (7), a spring element (8), and a valve part (9), whereby the magnet part has at least one magnetic coil (4) wound on a coil form (3), a flux concentrating element (5) and a center pole (6), and the valve part (9) has a closing element (11) that cooperates with the armature element (7) and controls the opening and closing of the valve on a valve seat (10), characterized in that the armature element (7) is designed as a clapper-type armature and cooperates with the center pole

(6) by way of a damping element (14), wherein the closing element (11) and the damping element (14) are designed as an integral damping shoe (15).

<sup>15</sup>  
~~9~~. (Previously amended) Valve according to claim <sup>17</sup>~~8~~, wherein the damping shoe (15) is flexible and can be attached directly to the armature element (7) or it is injection molded to it.

<sup>19</sup>  
~~10~~. (Previously added) Electromagnetically actuatable valve (1) comprising a magnet part (2), a moveable armature element (7), a spring element (8), and a valve part (9), whereby the magnet part has at least one magnetic coil (4) wound on a coil form (3), a flux concentrating element (5) and a center pole (6), and the valve part (9) has a closing element (11) that cooperates with the armature element (7) and controls the opening and closing of the valve on a valve seat (10), characterized in that the armature element (7) is designed as a clapper-type armature and cooperates with the center pole (6) by way of a damping element (14), wherein the closing element (11) and the damping element (14) are designed as an integral damping shoe (15).